

PART NO. 5205 (FENDERWELL)

DODGE DART/SWINGER/ DEMON 383-440
PLYMOUTH CUDA 383

NOTE: WILL NOT FIT WITH AIR CONDITIONING.

THANK YOU FOR MAKING HOOKER HEADERS YOUR CHOICE IN A HIGH PERFORMANCE EXHAUST SYSTEM. EXTENSIVE DYNO/TRACK TESTING HAS ENABLED HOOKER TO OFFER THE MOST ADVANCED DESIGN IN HEADERS FOR YOUR APPLICATION. DUE TO THE RESTRICTED ROOM AVAILABLE IN THE ENGINE COMPARTMENT, YOUR HEADERS MAY BE CLOSE TO SOME BODY AND CHASSIS COMPONENTS. THIS CONDITION IS NORMAL. INSTALLATION (WHILE NOT COMPLEX) MAY BE TIME CONSUMING. HOWEVER, AS SOON AS YOU START YOUR ENGINE THE ADDITIONAL HORSEPOWER AND IMPROVED PERFORMANCE WILL MORE THAN JUSTIFY YOUR EFFORTS. PROPER INSTALLATION AND MAINTENANCE WILL INSURE LONG LIFE AND MAXIMUM PERFORMANCE FROM YOUR HOOKER HEADERS.

BEFORE STARTING

YOUR VEHICLE MUST BE RAISED A MINIMUM OF 36 INCHES. A FLOOR HOIST IS IDEAL. IF NO HOIST IS AVAILABLE, WE STRONGLY URGE THE USE OF AXLE STANDS AS A SAFETY MEASURE. CAUTION! YOUR CAR SHOULD NOT BE SUPPORTED ON A BUMPER JACK.

INSTALLATION PROCEDURE - PLEASE READ CAREFULLY

LEFT SIDE

1. DISCONNECT BATTERY TO PREVENT ELECTRICAL SYSTEM DAMAGE.
2. UNBOLT STOCK HEADPIPE FROM EXHAUST MANIFOLD. DRAIN RADIATOR. (COOLANT MAY BE REUSED IF DRAINED INTO A CLEAN CONTAINER).
3. REMOVE SPARK PLUGS, EXHAUST MANIFOLD AND STUDS FROM HEADS.
4. USE AN AIR CHISEL OR CUTTING TORCH TO CUT A HOLE IN FENDER PANEL. SEE ILLUSTRATION 'A'.
5. START FROM UNDER FENDER AND WORK HEADER UP AND THROUGH HOLE INTO POSITION (THE INNER-FENDER PANEL MAY HAVE TO BE DENTED FOR CLEARANCE DUE TO VARIATION IN ENGINE LOCATION. SEE ILLUSTRATION 'C'.)
6. PLACE GASKET INTO POSITION AND START ALL BOLTS. TIGHTEN ALL BOLTS EVENLY.

RIGHT SIDE

1. UNBOLT STOCK HEADPIPE FROM EXHAUST MANIFOLD.
2. REMOVE SPARK PLUGS, EXHAUST MANIFOLD AND STUDS FROM HEADS.
3. CUT HOLE IN FENDER PANEL. SEE ILLUSTRATION 'B'.
4. STARTING FROM FENDER, WORK HEADER UP AND THROUGH HOLE IN POSITION.
5. PLACE GASKET INTO POSITION AND START ALL BOLTS.
6. TIGHTEN ALL BOLTS EVENLY.
7. REPLACE SPARK PLUGS (BOTH SIDES).
8. FILL RADIATOR.
9. TO CONNECT COLLECTORS TO HEADPIPES, PURCHASE HOOKER HEADER REDUCER KIT NO. 11035.
NOTE: DUAL EXHAUST SYSTEM CAN BE FABRICATED USING EITHER HOOKER SUPER COMPETITION TURBO MUFFLER, #21105 OR #21106; HOOKER COMPETITION TURBO #21005 OR #21006; OR UNIVERSAL HOOKER MUFFLER AND UNIVERSAL TAILPIPE.
10. CONNECT BATTERY, START ENGINE AND CHECK FOR LEAKS. BE SURE ALL BRAKE LINES, FUEL LINES, AND ELECTRICAL WIRES HAVE SUFFICIENT CLEARANCE. REROUTE AS NECESSARY.

WHEN FINISHED, GIVE YOUR CAR A TEST DRIVE CHECKING CAREFULLY FOR ANY NEW NOISES. AFTER SEVERAL DAYS DRIVING, RETIGHTEN ALL BOLTS.

ANY QUESTIONS? PLEASE CONTACT THE CUSTOMER SERVICE DEPARTMENT AT: HOOKER HEADERS, 1-866-464-6553

DID YOU KNOW THERE IS MORE TO HOOKER THAN JUST HEADERS? OF COURSE, WE LOVE OUR HOOKER HEADERS, BUT HOOKER BUILDS MORE THAN THE ULTIMATE IN HIGH PERFORMANCE EXHAUST SYSTEMS. ASK YOUR DEALER.



Super Competition

WARNING! Breaking in an engine with ceramic-coated headers **WILL** result in damage to the coating and will **VOID** all warranties. Ceramic-coated headers require several heat cycles to fully cure before they will withstand extreme heat. Flowtech® & Hooker® recommend using cast iron exhaust manifolds or old headers to break in new engines to avoid coating damage. Please call tech service at 270-781-9741 for additional information regarding ceramic-coated exhaust products.

LIMITATION OF LIABILITY - DISCLAIMER: THE REGULATION OF EMISSIONS PRODUCTION, NOISE LEVELS AND SAFETY STANDARDS IS UNDERTAKEN BY THE FEDERAL GOVERNMENT, EACH OF THE FIFTY STATE LEGISLATURES AND BY MANY LOCAL MUNICIPALITIES, TOWNS AND COUNTRIES.

HOOKER INDUSTRIES MAKES NO WARRANTIES OF MERCHANTABILITY, OF FITNESS FOR PARTICULAR PURPOSE, OR THAT ITS PRODUCTS ARE APPROVED FOR GENERAL USE, OR THAT ITS PRODUCTS COMPLY WITH LAWS, REGULATIONS OR ORDINANCES IN THE STATES WHERE THEY MAY BE SOLD TO THE ULTIMATE PURCHASER, THE CONSUMER.

UNLESS EXPRESSLY STATED TO THE CONTRARY IN THE CATALOG, INSTRUCTION SHEET OR PRICE LIST, THE ENTIRE RISK AS TO THE CONFORMITY OF ANY COMPANY PRODUCT IN ANY SUCH STATE AND AS TO REPAIR SHOULD THE PRODUCT PROVE TO BE DEFECTIVE OR NONCONFORMING, IS ON THE RETAIL PURCHASER, THE BUYER, THE ULTIMATE CONSUMER, OF SUCH PRODUCT AND IT IS NOT UPON THE SELLER, DISTRIBUTOR OR MANUFACTURER.

IN THIS CONNECTION, THE RETAIL PURCHASER, THE BUYER, THE ULTIMATE CONSUMER ASSUMES THE BURDEN OF THE ENTIRE COST OF ANY AND ALL NECESSARY SERVICE, ALTERATIONS OR REPAIR.

THE FOREGOING STATEMENT LIMITS THE LIABILITY OF THE MANUFACTURER.

CALIFORNIA VEHICLE CODE SECTIONS 27156 AND 38391 PROHIBIT THE ADVERTISING, OFFERING FOR SALE, OR INSTALLATION OF ANY DEVICE WHICH MODIFIES A VEHICLE'S EMISSION CONTROL SYSTEM UNLESS EXEMPTED. UNLESS OTHERWISE NOTED, HOOKER HEADERS HAVE NOT RECEIVED AN EXEMPTION FROM THESE CODE SECTIONS AND ARE NOT LEGAL FOR SALE OR USE IN CALIFORNIA ON VEHICLES ORIGINALLY EQUIPPED WITH CATALYTIC CONVERTERS. IT IS ILLEGAL, EXCEPT FOR RACING VEHICLES WHICH MAY NEVER BE DRIVEN UPON A HIGHWAY, TO REMOVE OR OTHERWISE RENDER INOPERATIVE ANY EMISSION CONTROL DEVICE ON REGULATED MOTOR VEHICLES-CHECK CATALOG LISTINGS TO INSURE PROPER APPLICATION. IN THE OTHER 49 STATES, UNLESS OTHERWISE NOTED, HOOKER HEADERS ARE NOT LEGAL FOR POLLUTION CONTROLLED MOTOR VEHICLES, EXCEPT FOR RACING VEHICLES WHICH MAY NEVER BE USED UPON A HIGHWAY AND ARE NOT INTENDED OR APPLICABLE FOR HIGHWAY USE.

